



























Laser head

Brand

Motor direction: Positive

8002

8.0000mm

Focus adjmt

Homing mode: Incremental Mode

0.60m/min

Model: BSD3/06/12/20/40/60K-CAT

40.00mm

0.00

32.00

32.00

Focus control port/servo

Node 5:调焦Axis

Use Chiller Drive

Restore default data

Manual Speed

Speed: 0.30m/min

Manual feed: 0.60m/min

Auto Speed

Speed: 6.00m/min

Acceleration: 1500.00mm/s²

Acc time: 100ms

OpticalRa... (1)100:200

ViewFirmwareVerAndCheckPar

Protective mirror alarm temperature setting

Protect Temp Alarm

Temp Alarm: 50.00 °C

Temp rise rate: 14.00 °C

OpticalRatioAndVer

Version: 2.22

Firmware: 2023

Gas Pressure Parameter Setting

Activate gas...

Deviation allowable...: 70.00 %

Temp rise rate: 14.00 °C

Deviation allowa... 20.00 %

Temp rise rate: 14.00 °C

Temp rise rate: 14.00 °C

Scattered light alarm设置

Scattered...

Temp increase Alarm: 200.00

Cavity Alarm Temperature Setting

Cav Temp Alarm

Temp: 40.00 °C

Temp: 50.00 °C

DewPointAlarmSet

Dewpoint Temp...



